



REQUEST FOR QUOTATION
(Shopping)

Name of Project : **Supply and Delivery of Maintenance Supplies**

Approved Budget for the Contract : **P600,000.00**

Deadline for Submission : **May 15, 2019**

Please quote your best quotation in line with the attached specifications. Suppliers are required to submit their valid and current Mayor's/Business Permit and PhiGEPS Registration Number.

Quotations shall be submitted in person to the Property Management Division, Administrative Services Department, PPA Corporate Bldg., Bonifacio Drive, South Harbor, Port Area, Manila. Quotations/documents sent to any other department/s or email address will not be considered.

For further information, please refer to:

The BAC Secretariat, Philippine Ports Authority
5th Floor, PPA Bldg., Bonifacio Drive
South Harbor, Port Area, Manila
Telephone/Fax No. 527-4735
954-88-00 loc. 539
PPA Website: www.ppa.com.ph

Very Truly Yours,

MARK JON S. PALOMAR
Chairperson, Bids and Awards Committee

Maintenance Supplies

Item No.	Specifications	Qty	Unit										
1	<p>Battery, size 3SMF D31-L, 12 volts, Built for hot climates (tropicalized), EGX technology and One (1) year warranty.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">RC</th> <th style="text-align: center;">Length</th> <th style="text-align: center;">Width</th> <th style="text-align: center;">Height</th> <th style="text-align: center;">Total Height</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">120</td> <td style="text-align: center;">304</td> <td style="text-align: center;">173</td> <td style="text-align: center;">203</td> <td style="text-align: center;">223</td> </tr> </tbody> </table>	RC	Length	Width	Height	Total Height	120	304	173	203	223	2	pc
RC	Length	Width	Height	Total Height									
120	304	173	203	223									
2	<p>Battery, size 2D/N120/F51, 12 volts, Calcium maintenance free battery, Constructed and designed to withstand extreme heat and vibration, High starting power and superior durability and Six (6) months warranty.</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: center;">RC</th> <th style="text-align: center;">Length</th> <th style="text-align: center;">Width</th> <th style="text-align: center;">Height</th> <th style="text-align: center;">Total Height</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">225</td> <td style="text-align: center;">504</td> <td style="text-align: center;">180</td> <td style="text-align: center;">210</td> <td style="text-align: center;">230</td> </tr> </tbody> </table>	RC	Length	Width	Height	Total Height	225	504	180	210	230	1	pc
RC	Length	Width	Height	Total Height									
225	504	180	210	230									
3	All Around Sealant , Elastomeric, solvent-release temperature curing sealant	2	liter										
4	Angle Bar size: 1 1/2" x 1 1/2" x 20 ft., 3mm thk	12	pc										
5	Angle Bar size: 2" x 2" x 10 ft., 3mm thk	1	pc										
6	Blind Rivets, size: 5/8" x 1", 100's per box	5	box										
7	Blind Rivets, size: 1/4" x 1", 100's per box	5	box										
8	Blind Rivets, size: 1/8" x 1", 100's per box	5	box										
9	Capacitor, 1.5MF / 450V	20	pc										
10	Capacitor, 6MF / 450V	20	pc										
11	Circuit Breaker NBD 400H 3300, 3P, 400A	3	pc										
12	Circuit Breaker QOB232VSC6, 2P, 32A	12	pc										
13	Circuit Breaker, 3P, 50A, Bolt-on	10	pc										
14	Circuit Breaker, 3P, 50A, Plug-in	10	pc										

15	Cotton Gloves with Rubber Coating	20	pair																																																			
16	Electrical Tape	10	roll																																																			
17	Epoxy A & B, 1 liter per can	2	set																																																			
18	Flexible Hose, size: 1/2" x 1/2" x 12", 304-Stainless Braided	50	pc																																																			
19	Flexible Hose, size: 1/2" x 1/2" x 16", 304-Stainless Braided	50	pc																																																			
20	Frosted Sticker size: 122 cm x 50 meters	1	roll																																																			
21	Gate Valve, size: 1/2", Dual, Brass	20	pc																																																			
22	Hacksaw Blade, 12 in, High-Tension	10	pc																																																			
23	Hose Bib, size: 1/2, Chrome	20	pc																																																			
24	Hydraulic Steering Fluid , Perfect blend of viscosity stabilizers, anti-wear agents and corrosion inhibitors will ensure maximum steering life performance	1	liter																																																			
25	<p>Hydraulic Hinges 3 RTS 85</p> <table border="1"> <thead> <tr> <th rowspan="2">Technical Data</th> <th colspan="3">RTS 65</th> </tr> <tr> <th>EN 3</th> <th>EN 4</th> <th>EN 5</th> </tr> </thead> <tbody> <tr> <td>Closing force</td> <td>EN 3</td> <td>EN 4</td> <td>EN 5</td> </tr> <tr> <td>Internal doors up to 950 mm and External doors 1100 mm 1250 mm</td> <td>Yes</td> <td>Yes</td> <td>Yes</td> </tr> <tr> <td>Same model for double action doors, RH (ISO 5) and LH (ISO 6)</td> <td>Yes</td> <td>Yes</td> <td>Yes</td> </tr> <tr> <td>Closing speed variable by valve adjustment</td> <td>Yes</td> <td>Yes</td> <td>Yes</td> </tr> <tr> <td>Final closing speed variable by valve adjustment</td> <td>Yes</td> <td>Yes</td> <td>Yes</td> </tr> <tr> <td>Backcheck, progressive, mechanical</td> <td>Yes</td> <td>Yes</td> <td>Yes</td> </tr> <tr> <td>Backstop, Mechanical</td> <td>Yes</td> <td>Yes</td> <td>Yes</td> </tr> <tr> <td>Hold-open 105° 190°</td> <td>Option</td> <td>Option</td> <td>Option</td> </tr> <tr> <td>Extended spindle 005 mm 010 mm</td> <td>Option</td> <td>Option</td> <td>Option</td> </tr> <tr> <td>Reduced pivot point for tempered glass doors (65mm)</td> <td>Option</td> <td>Option</td> <td>Option</td> </tr> <tr> <td>Weight in kg</td> <td>4.7</td> <td>4.8</td> <td>4.9</td> </tr> </tbody> </table>	Technical Data	RTS 65			EN 3	EN 4	EN 5	Closing force	EN 3	EN 4	EN 5	Internal doors up to 950 mm and External doors 1100 mm 1250 mm	Yes	Yes	Yes	Same model for double action doors, RH (ISO 5) and LH (ISO 6)	Yes	Yes	Yes	Closing speed variable by valve adjustment	Yes	Yes	Yes	Final closing speed variable by valve adjustment	Yes	Yes	Yes	Backcheck, progressive, mechanical	Yes	Yes	Yes	Backstop, Mechanical	Yes	Yes	Yes	Hold-open 105° 190°	Option	Option	Option	Extended spindle 005 mm 010 mm	Option	Option	Option	Reduced pivot point for tempered glass doors (65mm)	Option	Option	Option	Weight in kg	4.7	4.8	4.9	6	pc
Technical Data	RTS 65																																																					
	EN 3	EN 4	EN 5																																																			
Closing force	EN 3	EN 4	EN 5																																																			
Internal doors up to 950 mm and External doors 1100 mm 1250 mm	Yes	Yes	Yes																																																			
Same model for double action doors, RH (ISO 5) and LH (ISO 6)	Yes	Yes	Yes																																																			
Closing speed variable by valve adjustment	Yes	Yes	Yes																																																			
Final closing speed variable by valve adjustment	Yes	Yes	Yes																																																			
Backcheck, progressive, mechanical	Yes	Yes	Yes																																																			
Backstop, Mechanical	Yes	Yes	Yes																																																			
Hold-open 105° 190°	Option	Option	Option																																																			
Extended spindle 005 mm 010 mm	Option	Option	Option																																																			
Reduced pivot point for tempered glass doors (65mm)	Option	Option	Option																																																			
Weight in kg	4.7	4.8	4.9																																																			

	<table border="1"> <tr> <td>Dimensions in mm</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Length</td> <td>323</td> <td>323</td> <td>323</td> </tr> <tr> <td>Width</td> <td>90</td> <td>90</td> <td>90</td> </tr> <tr> <td>Height</td> <td>38</td> <td>38</td> <td>38</td> </tr> <tr> <td>Door closer tested to EN 1154</td> <td>Yes</td> <td>Yes</td> <td>Yes</td> </tr> </table>	Dimensions in mm				Length	323	323	323	Width	90	90	90	Height	38	38	38	Door closer tested to EN 1154	Yes	Yes	Yes		
Dimensions in mm																							
Length	323	323	323																				
Width	90	90	90																				
Height	38	38	38																				
Door closer tested to EN 1154	Yes	Yes	Yes																				
26	LAN Cable CAT 5E, 150 meters per box	1	box																				
27	LED Pin Type, MR16, 4W, Daylight, with One (1) year warranty	50	pc																				
28	LED Ecomax Bulb EI A70 12W E27/B22, 6500K, 1150lm, 220-240V, Daylight, with One (1) year warranty	56	pc																				
29	LED T5 Batten 16W, 165-250V, 1200mm, 1500lm, Daylight, with One (1) year warranty	73	pc																				
30	LED T5 Batten 16W, 165-250V, 1200mm, 1500lm, Warm White, with One (1) year warranty	50	pc																				
31	LED Ecomax Bulb EI A60 9W E27/B22, 6500K, 850lm, 220-240V, Daylight, with One (1) year warranty	65	pc																				
32	LED Flood Light Ecomax 2, 100W, IP65, 220-240V, Outdoor, Daylight, with One (1) year warranty	3	pc																				
33	Magnetic Contactor, 50A, 3P, 230V, 10KW PAK-26J, Dimension: 1.1 x 0.8 x 0.9 cm, Thermal overload relay and Contactor Screw size: M5, Thermal overload relay applicable and Contactor applicable wire size diameter: 1.6-3.2 mm, Thermal overload relay and Contactor Tightening torque: 2.4-3.5Nm	3	pc																				
34	Miniature Circuit Breaker A9K27232, 2P, 32A	12	pc																				
35	Miniature Circuit Breaker, 2P, 40A	12	pc																				
36	Motor Oil for change oil	10	liters																				
37	P Trap, size: 1 1/2", with Clean out, Stainless Steel	20	pc																				
38	Paint Brush 2"	5	pc																				

39	Paint Roller with handle , size: 9"	5	pc
40	Penetrant Spray with smart straw, 12oz	3	can
41	PVC Pipe Cement (200cc)	5	can
42	RJ 45 LAN Connector (Female)	200	pc
43	RJ 45 LAN Connector (Male)	200	pc
44	Silver Rod	50	pc
45	Soft Rubber Matting – Loop spaghetti, size: 45cm x 75cm	30	pc
46	Stainless Steel Douche Hygienic Spray	20	set
47	Steel Matting, Sheet size: 4 ft. x 8 ft., Mesh size: 2" x 2", Wire dia. Size: 5.5mm	7	pc
48	Strainer, Flip Drain Stopper Type, size: 1 1/4", Stainless	30	pc
49	Teflon Tape, size: 1/2"	30	roll
50	Terminal Block 600V, IN411S, 600V max, 14mm ²	5	pc
51	Terminal Block 600V, IN30BK, 600V max, 8mm ²	5	pc
52	Universal Convenience Outlet – 3 gang with plate	15	pc
53	UTP Cable Cat6, 150 meters per box	1	box
54	Vertical Pressure Tank, Stainless Steel, 82 - Gal. capacity	1	unit
55	Water Soluble Degreaser	1	liter
56	Water Hose, 1/2	30	meter
57	Welding Rod N55 6013	10	kilo

Delivery: Shall be completed within fifteen (15) working days from receipt of Purchase Order.