

**REQUEST FOR QUOTATION**


**NAME OF SUPPLIER:**

**QUOTATION NO.:** 0073-2019

**OFFICE ADDRESS :**

**DATE PREPARED:** June 06, 2019

Please quote your lowest price on the item/s listed below, subject to the General Condition on the last page, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than \_\_\_\_\_.



**RANDY B. VILLARTE**  
 Actg. Supervising Supply Officer

**NOTE:**

1. All entries must be handwritten or typewritten
2. Delivery period within 30 calendar days.
3. Warranty shall be for a period of six (6) months for supplies & materials, one (1) year for equipment, from date of acceptance by the procuring entity.
4. Price validity shall be for a period of 30 calendar days
5. G-EPS registration certificate shall be attached upon submission of the quotation
6. Bidders shall submit original brochures showing certifications of the product being offered.
7. Sealed/Unsealed canvasses/quotation shall be accepted
8. All prospective bidders shall submit Mayor's/Business permit, PhilGEPS registration number, Income/Business Tax Returns, Omnibus sworn statement and DTI certificate of registration during the opening of sealed RFQ.

ITEM NO.	ITEM & DESCRIPTION	QTY	UNIT	PRICE/ UNIT	TOTAL AMOUNT
1	<b>REPOSTING FOR THE PROCUREMENT OF:</b>				
	<b>ANEMOMETER, HIGH QUALITY, BRANDED</b>	1	UNIT		
	<b>WITH THE FOLLOWING SPECS:</b>				
	-DISPLAY ERROR ≤ 3% (F.S.)				
	-ACTION ERROR ≤ 2% (F.S.)				
	-AC 220V ± 15%				
	-INSULATING ABILITY ≥ 10 M Ω				
	-POWER CONSUMPTION ≤ 20 W				
	<b>-OUTDOOR WORK ENVIRONMENT:</b>				
	-TEMPERATURE 30°C ~ + 60°C				
	-HUMIDITY 90%				
	<b>-INDOOR WORK ENVIRONMENT</b>				
	-TEMPERATURE 5°C ~ + 50°C				
	-HUMIDITY 90%				
	-IP GRADE: IP 64				
	<b>-OUTPUT SIGNAL</b>				
	-SWITCH SIGNAL				
	-4-20 mA SIGNAL				
	-RS 485 SIGNAL				
	-ALARM VOICE > 60db				
	-POWER CONSUMPTION ≤ 35 W				
	<b>FITTING/WIND SENSOR</b>				
	-MEASUREMENT RANGE 1.0-60 m/s				
	-ACCURACY < 30m/s ± (0.5 + 0.05V) ≤ 30m/s ± 5%				
	-RESOLUTION 0.1 m/s				
	-STARTING WIND SPEED < 0.7 m/s				
	-WORK ENVIRONMENT -30°C ~ + 60°C				
	-SIGNAL STRENGTH TTL IMPULSE				
	<b>FITTING/WIND DIRECTION SENSOR</b>				
	-MEASUREMENT RANGE 16 DIRECTIONS (360°)				
	-MEASUREMENT ACCURACY ± 5%				
	-INPUT VOLTAGE DC 5V ~ 24V DC				
	<b>Approved ABC: Php 90,000.00</b>				
	xxx nothing follows xxx				

Brand and Model :

Delivery Period:

Warranty :

Price Validity:

After having carefully read and accepted your General Conditions, I/We quote you on the item at prices noted above.

PRINTED NAME/SIGNATURE

Canvassed by: \_\_\_\_\_

TEL NO. / CELLPHONE NO.

Date canvassed : \_\_\_\_\_

DATE